

Biometric Tripod Turnstile



TS2000 Tripod Turnstile

TS2011 Tripod Turnstile with Controller and RFID Reader

TS2022 Tripod Turnstile with Controller and Fingerprint & RFID Reader

Tripod turnstiles are compact and cost-effective entrance solutions. Designing for smooth and silent operation, reducing power consumption, wear and tear. It is suitable for areas with a high traffic.

The TS2000 series offer a well-designed, two-legged casework made of stainless steel, ideal for sites where a high traffic and robustness are issued.

By receiving a signal from the access control system, or pushing button, it allows the entry of one person in a time. Entering into different directions are electronically controlled. Default mode is to lock the mechanism until a valid authorization signal is received. If you want to set one side free, you can adjust the mechanism. In case of emergency, the horizontal arm will drop to allow free passage. Led way mode indicators are included as standard.

Features




Reliability

- Alloy steel tripod hub prevents mechanical wear
- Casework and tripod arms manufactured in SUS304 stainless steel
- Electromagnets for lock are used only when being activated. They are in standby mode when the device is idle.
- ZK patented compact mechanism ensures
- High quality electrical components




Safety and User-Orientated Design

- Drop arm designed for emergency purpose
- No exposed screws, safer for the user.
- Smooth operation designed for mass transit application
- The pictogram on the device indicating access permission and direction of movement
- Special designed case shape, user-friendly for passenger to punch card or finger.
- Anti-tailgate



Easy Integration

- Flexible reader installation plate. Customers can easily integrate with third party reader
- Standard electrical interface for third party device.
- Using compact mechanism, the turnstile has more space inside for integration
- ZKTeco provides integration service in factory, with board and peripherals installed, ensuring compliance of the system. When the turnstile is delivered, just plug it in and do the setting. Save the cost of installation.
- The design of being vacuum at the bottom part of the device, enables easy installation for other hardwares.




Specifications

Power Supply	AC 220V/110V, 50/60Hz
Operating Temperature	-28 °C- 60 °C
Operating Humidity	5%-85%
Working Environment	Indoor
Rated Power	60W
Flow Rate	25- 48 passage/minute
Casework Material	SUS304
Pictogram Indication	Yes
Control System	Input controlled by dry contact
Emergency Button Input	Yes
Dimension	111×98×26(CM) + arm length 50CM
Package Dimension	120×108×38(CM)
Net Weight	46KG
Gross Weight with Package	54KG
Optional Function	Alternative material or shape, third-party access control integration, ticket system integration, passage counter

Model	TS2000	TS2011	TS2022
Access Control	N/A	C3-200	InBio260
Reader	N/A	2*KR100E	2*FR1200
Card Capacity	N/A	30,000	30,000
Fingerprint Capacity	N/A	N/A	3,000
Event Capacity	N/A	100,000	100,000

Dimensions (mm)



ZKTeco Europe
www.zkteco.eu



© Copyright 2015. ZKTeco Inc. ZKTeco Logo is a registered trademark of ZKTeco or a related company. All other product and company names mentioned are used for identification purposes only and may be the trademarks of their respective owners. All specifications are subject to change without notice. All rights reserved.