

Biometric Full Height Turnstile

FHT2400: Full Height Turnstile FHT2411: Full Height Turnstile with RFID Access Control System FHT2422: Full Height Turnstile with Fingerprint and RFID Access Control System



Application









Industrial facility

Corporate security

Government security

Public transportation

Specifications

| Power requirements | | AC110V/220V, 50/60Hz |
|----------------------------|-------------|----------------------------|
| Working temperature | | -28℃~60℃ |
| Working humidity | | 0%~95% |
| Working environment | | Indoor/Outdoor |
| Speed of throughput | RFID | Maximum 30/minute |
| | Fingerprint | Maximum 25/minute |
| | Face | Maximum 15/minute |
| | Vein | Maximum 15/minute |
| Lane width(mm) | | 580 |
| Footprint(mm*mm) | | 1400*1320 |
| Dimension(mm) | | L=1400 W=1320 H=2220 |
| Dimension with packing(mm) | | 1975x925x895&2100x1435x470 |
| LED indicator | | Y |
| Cabinet material | | SUS304 Stainless Steel |
| Barrier material | | SUS304 Stainless Steel |
| Barrier movement | | Rotating |
| Emergency mode | | Y |
| Security level | | High |
| MCBF | | 2 million |
| Ingress protection | | IP54 |

Dimensions (mm)





ZKTECO CO.,LTD. E-mail: sales@zkteco.com www.zkteco.com © Copyright 2015. ZKTECO CO, LTD. ZKTeco Logo is a registered trademark of ZKTeco or a related company. All other product and company names mentioned are used for identification purposes only and may be the trademarks of their respective owners. All specifications are subject to change without notice. All rights reserved.

